

Precision Rotative Transducers, Conductive Plastic, Economic Series (ECO)



The “ECO” models are a comprehensive range of rotational motion transducers for industrial applications.

All mechanical and electrical parameters can be adapted to meet your specifications.

FEATURES

- Size 05 - 09 - 13 are available
- Long life up to 30 million cycles
- Accuracy $\pm 1\%$ down to $\pm 0.25\%$
- Bush or servo mounting types
- Rear mounted terminals
- Following MIL-R-39023 and NFC 93-255 requirements
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

QUICK REFERENCE DATA

| | |
|------------------|--------------------------------|
| Sensor type | ROTATIONAL, conductive plastic |
| Output type | Output by turrets |
| Market appliance | Industrial |
| Dimensions | Various sizes |

| SIZE | 05 | | 09 | | | 13 | | |
|-------|-------|-------|-------|-------|-------|--------|--------|--------|
| MODEL | 50 ES | 50 CB | 78 ES | 78 CS | 78 CB | 156 ES | 156 CS | 156 CB |

| ELECTRICAL SPECIFICATIONS | | | | | | | |
|------------------------------------|---|--------------|------------------------------|--------------|-------------------------------|--------------|--|
| Theoretical electrical angle (TEA) | Actual electrical angle (AEA) - 2° | | | | | | |
| Independent linearity (over TEA) | A $\leq \pm 1\%$ (standard) | | B $\leq \pm 0.5\%$ (special) | | C $\leq \pm 0.25\%$ (special) | | |
| Actual electrical angle (AEA) | 330° $\pm 5^\circ$ | | 340° $\pm 5^\circ$ | | 350° $\pm 5^\circ$ | | |
| Ohmic values (R _T) | 1 k Ω - 5 k Ω - 10 k Ω - on request other values | | | | | | |
| Ohmic value tolerances at 20 °C | $\pm 10\%$ | $\pm 20\%$ | $\pm 10\%$ | $\pm 20\%$ | $\pm 10\%$ | $\pm 20\%$ | |
| Output smoothness | $\leq 0.05\%$ | | | | | | |
| Maximum power rating at 70 °C | 0.2 W | | 0.3 W | | 0.5 W | | |
| Wiper current | Recommended: a few μ A - 1 mA max. (continuous) | | | | | | |
| Tap (current or voltage) | NA | | 1 (on request) | | | | |
| Resistance load on wiper | Minimum 10 ³ x R _T | | | | | | |
| End voltage | $\leq 0.2\%$ | $\leq 0.5\%$ | $\leq 0.2\%$ | $\leq 0.5\%$ | $\leq 0.2\%$ | $\leq 0.5\%$ | |
| Insulation resistance | $\geq 1000\text{ M}\Omega$, 500 V _{DC} | | | | | | |
| Dielectric strength | $\geq 500\text{ V}_{\text{RMS}}$, 50 Hz | | | | | | |

| MECHANICAL SPECIFICATIONS | | | | | | | |
|--|-------------------------------------|-----------------|--------------------|-----------------|--------------------|-----------------|--|
| Mechanical angle (MA) | 360° continuous | | | | | | |
| On request: stops | NA | | 340° $\pm 3^\circ$ | | 350° $\pm 3^\circ$ | | |
| Mounting type | Servo | Bushing | Servo | Bushing | Servo | Bushing | |
| Shaft guiding | Ball bearings | Sleeve bearings | Ball bearings | Sleeve bearings | Ball bearings | Sleeve bearings | |
| Shaft | Stainless steel | | | | | | |
| Housing | Plastic molding | | | | | | |
| Termination | Turrets | | | | | | |
| Wiper | Precious metal multi-finger contact | | | | | | |
| Starting torque (N.cm) | ≤ 0.2 | ≤ 0.5 | ≤ 0.2 | ≤ 0.5 | ≤ 0.2 | ≤ 0.5 | |
| Torque on stops (N.cm) | 50 | | | | | | |
| Weight (g) | 5 ± 2 | 8 ± 2 | 13 ± 2 | 17 ± 2 | 29 ± 2 | 34 ± 2 | |
| Moment of inertia (g cm ²) | ≤ 0.5 | | ≤ 1 | | ≤ 2 | | |

| PERFORMANCE | | |
|-------------------------------|--------------------------------------|---------------------------|
| Life (10 ⁶ cycles) | 30 (on ES models) | 20 (on CS and CB models) |
| Temperature range | -55 °C to +125 °C | |
| Climatic category | 55/125/04 | |
| Speed rotation (RPM) | 600 (on ES models) | 150 (on CS and CB models) |
| Sine vibration on 3 axes | 1.5 mm or 20 g from 10 Hz to 2000 Hz | |
| Mechanical shocks on 3 axes | 50 g - 11 ms - half sine | |

Note


- Nothing stated herein shall be construed as a guarantee of quality or durability.

DIMENSIONS in millimeters, general tolerance ± 0.5 mm

SIZE 05/09/13

SERVO MOUNT TYPE

- 50 ES
- 78 ES
- 78 CS
- 156 ES
- 156 CS




| DIMENSIONS | DESIGNATION | SIZE 05 | SIZE 09 | | SIZE 13 | |
|------------|----------------------|-----------|---------|-------|-----------|--------|
| | | 50 ES | 78 ES | 78 CS | 156 ES | 156 CS |
| Ø A | Ø housing | 12.7 | 22.2 | | 33.3 | |
| B | Length | 13.0 | 13.5 | | 18.0 | |
| Ø C | Ø pilot | 9.525 | 19.05 | | 30.16 | |
| Ø D max. | Ø groove | 11.45 | 19.64 | | 30.9 | |
| F | Flange thickness | 1 ± 0.1 | | | 1.6 ± 0.1 | |
| G | Shoulder | 1.2 ± 0.1 | | | 1.6 ± 0.1 | |
| H | Dia. of groove | 1.2 ± 0.2 | | | 1.5 min. | |
| I max. | Height of the turret | 2.5 | 2.5 | | 3.6 | |

SIZE 05/09/13

BUSHING MOUNT TYPE

- 50 CB
- 78 CB
- 156 CB




| DIMENSIONS | DESIGNATION | SIZE 05 | SIZE 09 | SIZE 13 |
|------------|-------------|---------|---------|---------|
| | | 50 CB | 78 CB | 156 CB |
| Ø A | Ø housing | 12.7 | 22.2 | 33.3 |
| B max. | Length | 11 | 11.5 | 16 |

DIMENSIONS in millimeters, general tolerance ± 0.5 mm

SIZE 05/09/13

SERVO MOUNT TYPE


- 50 ES
- 78 ES
- 78 CS
- 156 ES
- 156 CS




| | | | | |
|--------|----------------------|-----|-----|-----|
| C max. | Height of the turret | 2.5 | 2.5 | 3.6 |
|--------|----------------------|-----|-----|-----|

DIMENSIONS in millimeters, general tolerance ± 0.5 mm



SIZE 05



SIZE 09



SIZE 13





| ORDERING INFORMATION/DESCRIPTION | | | | | | | |
|----------------------------------|-------|--|------------------------|---------------------------------------|---|--|-------------|
| ECO | 78 | E | S | A | T | 103 | e4 |
| SERIES | MODEL | TYPE | FIXATION | LINEARITY CODE | TAP | OHMIC VALUE | LEAD FINISH |
| | | E = Ball bearings C = Sleeve bearings | S: Servo B: Bushing | A: ± 1 % B: ± 0.5 % C: ± 0.25 % | On request T: Voltage U: Current position to be specified | First 2 digits are significant numbers 3 rd digit indicates number of zeros | |

Special characteristics and designs on request

| SAP PART NUMBERING GUIDELINES | | | |
|-------------------------------|-------|-----------|-------------|
| ECO | 78CB | C | 502 |
| SERIES | MODEL | LINEARITY | OHMIC VALUE |
| | | | |



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.